

BLACK 14 GA IN LOWER FRT. LOAD CTR. BREAKER "13"
 BROWN 14 GA IN BATTERY COMP. ON WLFC
 YELLOW 14 GA IN LUGGAGE COMP. ON WLPP

ON-OFF SWITCH; LOCATE IN
 AUX. SPACE IN UPPER DASH

RIGHT (B1) 2268522 LEFT

12 VDC

(A1) SPOTLIGHT DIRECTIONAL CONTROL

(B2) SOCKET 2240794

SPOT FLOOD LT SWITCH
 ON-OFF-ON

(B3) 2268548

SPEED CONTROL

BROWN "43
 16 GA.


RED "43
 16 GA.

SPOT LT
 COMM.
 FLOOD LT

LEFT

RIGHT

(B1) RELAY P/N 2240718



(B1) SPOT-FLOOD LT 2206365

(B1) NOTE:
 ONE SPEED; DIRECTIONAL CONTROL IS SUPPLIED
 WITH P/N 2206365. ONLY ONE SPEED; DIREC
 TIONAL CONTROL IS REQUIRED PER DUAL SPOT LT INSTALLATION.

REV.	WAS	REVISIONS	BY	DATE	REL.
B-1	-	ADDED PIN 1 NOTES	C.S.	10-23-82	
A-3	-	REVERSED WIRES	C.S.	8-13-82	
A-2	-	CHANGED GROUND LOCATION	C.S.	10-15-81	
A-1	-	ADDED GROUND	C.S.	10-15-82	

RELEASED BY: Blue Bird Wanderlodge, Inc. SCALE: FORT VALLEY, GEORGIA, U.S.A.

DIAGRAM - WIRING; DUAL SPOTLIGHT CONTROL

DR. 47-14-82 BY: [Signature] SIZE: 2749918

TOLERANCE ON ALL DIMENSIONS IS, PLUS OR MINUS UNLESS OTHERWISE SPECIFIED.

INACTIVATES NOS.