ON-OFF SWITCH; LOCATE IN AUX. SPACE IN UPPER DASH

RIGHT (B1) 2268522 LEFT

12 VDC

BLACK 14 GA IN LOWER FRT LOAD CTR BREAKER #13

(A1) BROWN 14 GA IN BATTERY COMP ON WLFC

YELLOW 14 GA IN LUGGAGE COMP ON WLPP

(A1) SPOTLIGHT DIRECTIONAL CONTROL

YELLOW

GREEN

BLUE

BROWN

(B1) SOCKET 2241144

	3	2	
	4	1	
	15	5	
	14	7	
	16	6	
	18	8	
	17	10	
	19	9	
	21	11	
	20	13	
	22	12	

BROWN
GREEN
BLUE
YELLOW

ORANGE
BLACK
GRAY

LEFT

RIGHT

SPOT & FLOOD LT SWITCH ON-OFF-ON

(B1) 2268548

SPEED CONTROL

BROWN #43 16 GA

LT

RED #13 16 GA

SPOT LT
COMM.
FLOOD LT

YELLOW

BROWN
GREEN
BLUE

ORANGE
BLACK
GRAY

(B1) RELAY P/N 2240178

22 12 13
20 21 11
19 9 10
17 18 8
16 6 7
14 15 5

4 3 2 1

(B1) SPOT-FLOOD LT 2206365

(B1) NOTE:
ONE SPEED & DIRECTIONAL CONTROL IS SUPPLIED WITH P/N 2206365. ONLY ONE SPEED & DIRECTIONAL CONTROL IS REQUIRED PER DUAL SPOT LT INSTALLATION.

CONFIDENTIAL
THE INFORMATION HEREON IS CONFIDENTIAL BUSINESS INFORMATION AND MAY NOT BE USED FOR ANY PURPOSE UNLESS SUCH USE IS EXPRESSLY GRANTED IN WRITING BY BLUE BIRD BODY COMPANY.
© 1987 BLUE BIRD BODY COMPANY
ALL RIGHTS RESERVED

DEC 06 1990

LET.	WAS	REVISIONS	BY	DATE	REL.
B1	–	ADDED P/N & NOTES	CS	10-22-82	
A3	–	REVERSED WIRES	CS	8-11-82	
A2	–	CHANGES GROUND LOCATION	CS	8-1-82	
A1	–	ADDED GROUND	CS	10-4-82	

RELEASED

Blue Bird Wanderlodge, Inc.
FORT VALLEY, GEORGIA, U.S.A.

SCALE

DIAGRAM - WIRING; DUAL SPOTLIGHT CONTROL

TOLERANCE ON ALL DIMENSIONS IS, PLUS ____ OR MINUS ____ UNLESS OTHERWISE SPECIFIED.

INACTIVATES NOS.

REPLACED BY NOS.

DR. 4-14-82 BY SHELTON

CK. 4-15-82 BY [illegible]

DO NOT SCALE

SIZE C

37499B