



1155142

REV 8 1994

CONFIDENTIAL
 THE INFORMATION HEREON IS CONFIDENTIAL BUS-
 INESS INFORMATION AND MAY NOT BE USED FOR ANY
 PURPOSE UNLESS SUCH USE IS EXPRESSLY GRANTED
 IN WRITING BY BLUE BIRD BODY COMPANY.
 © 1984 BLUE BIRD BODY COMPANY
 ALL RIGHTS RESERVED

KEY	SERVICE PERIOD	CHECK	DESCRIPTION	GENERAL INSTRUCTIONS	RECOMMENDED LUBRICANT
8.	ONCE AT 4,000 MILES	—	FRONT AXLE	4-FITTINGS-NO PERIODIC MAINTENANCE REQUIRED	NI-GI GRADE NO. 2
9.	*15,000 MILES OR 3 MONTHS	—	PROPELLOR SHAFT UNIVERSAL JOINT	1-FITTING-EACH JOINT USE LOW PRESSURE	NI-GI GRADE NO. 2
10.	*15,000 MILES OR 3 MONTHS	—	PROPELLOR SHAFT SLIP JOINT	1-FITTING-USE LOW PRESSURE	NI-GI GRADE NO. 2
11.	*50,000 MILES OR 6 MONTHS	—	BRAKE CAMSHAFT	4-FITTINGS	NI-GI GRADE NO. 2
12.	*50,000 MILES OR 6 MONTHS	—	BRAKE SLACKADJUSTER	4-FITTINGS	NI-GI GRADE NO. 1 (SPECIAL STOPMASTER GREASE)
13.	—	—	TIE ROD ENDS	PERMANENTLY LUBRICATED	—

* WHICHEVER OCCURS FIRST

KEY	SERVICE PERIOD	CHECK	DESCRIPTION	GENERAL INSTRUCTION	RECOMMENDED LUBRICANT
1.	SEE OWNERS MANUAL	DAILY	ENGINE OIL	CHECK LEVEL.	FOLLOW ENGINE MANUFACTURER'S RECOMMENDATIONS FOR S. A. E. GRADE
2.	SEE OWNERS MANUAL	—	ENGINE OIL FILTER	—	FOLLOW ENGINE MANUFACTURER'S RECOMMENDATION
3.	*25,000 MILES OR 6 MONTHS	1,000 MILES	REAR AXLE	KEEP OIL TO LEVEL OF FILLER PLUG, DRAIN AND REFILL AT FIRST 1,000 TO 3,000 MILES AND THEN AT RECOMMENDED INTERVALS. CHECK LEVEL TESTING PLUG IN SIDE OF CARRIER HOUSING	HYPOID GEAR OIL S. A. E. 140 OR S. A. E. 85W/140 OR S. A. E. 80W/140
4.	ONCE A YEAR	1,000 MILES	WHEEL BEARINGS FRONT AXLE	CHANGE LUBRICANT WHENEVER SEALS ARE REPLACED OR WHEN BRAKES ARE RELINED OR AT LEAST ONCE A YEAR.	HYPOID GEAR OIL S. A. E. 85W/90
5.	NOT REQUIRED	5,000 MILES	HYDRAULIC POWER STEERING PUMP	NO PERIODIC MAINTENANCE REQUIRED	DEXTRON II
6.	SEE GENERAL INSTRUCTIONS	MONTHLY	AUTOMATIC TRANSMISSION (ALLISON)	EXTERNAL FILTER-FIRST 5,000 MILES, THEN EVERY 25,000 MILES OR 6 MONTHS. INTERNAL FILTER-FIRST OIL CHANGE, THEN AT 500,000 MILES OR OVERHAUL. OIL-100,000 MILES OR 12 MONTHS.	DEXTRON OR DEXTRON II
7.	*5,000 MILES OR 6 MONTHS	—	STEERING LINKAGE (FRAG ROD)	5-FITTINGS	NI-GI GRADE NO. 2

MATERIAL:

PLAT SIZE:

FINISH: PAINT PLATING PRIME OTHER MILLIMETRE / INCH

COLOR OR TYPE:

DO NOT SCALE: MILLIMETRE / INCH

TOLERANCE ON ALL DIMENSIONS IS PLUS OR MINUS: UNLESS OTHERWISE SPECIFIED

INACTIVATES NOS:

REPLACED BY NOS:

DIAGRAM, LUBRICATION GUIDE, CHASSIS, 1754 MODEL

DR 3-G-84BY AWS SIZE 1155142

CR BY C

REV