



1155159

KEY	SERVICE PERIOD	CHECK	DESCRIPTION	GENERAL INSTRUCTION	RECOMMENDED LUBRICANT
1.	SEE OWNERS MANUAL	DAILY	ENGINE OIL	CHECK LEVEL	FOLLOW ENGINE MANUFACTURER'S RECOMMENDATIONS FOR S.A.E. GRADE
2.	SEE OWNERS MANUAL	—	ENGINE OIL FILTER	FOLLOW ENGINE MANUFACTURER'S RECOMMENDATION	—
3.	*25,000 MILES OR 6 MONTHS	1,000 MILES	REAR AXLE	KEEP OIL TO LEVEL OF FILLER PLUG, DRAIN AND REFILL AT FIRST 1,000 TO 3,000 MILES AND THEN AT RECOMMENDED INTERVALS. CHECK LEVEL TESTING PLUG IN "DOWN" OF AXLE	HYPOID GEAR OIL S.A.E. 140 OR S.A.E. 90/140 OR S.A.E. 80W/140
4.	ONCE A YEAR	1,000 MILES	WHEEL BEARINGS FRONT AXLE AND TAG AXLE	CHANGE LUBRICANT WHENEVER SEALS ARE REPLACED OR WHEN BRAKES ARE BELINED OR AT LEAST ONCE A YEAR.	HYPOID GEAR OIL S.A.E. 90/90
5.	*25,000 MILES OR 6 MONTHS	5,000 MILES OR MONTHLY	HYDRAULIC POWER STEERING & PUMP	CHECK LEVEL AT RESERVOIR DIPPING. CHANGE OIL & FILTER AT REGULAR SERVICE INTERVALS, OR WHEN BYPASS INDICATOR IS IN THE "RED" AT FULL THROTTLE WITH SYSTEM WARM.	TEXACO BAWLES MOTOR OIL S.A.E. 150/50
6.	SEE GENERAL INSTRUCTIONS	MONTHLY	AUTOMATIC TRANSMISSION (ALLISON)	EXTERNAL FILTER—FIRST 5,000 MILES THEN AT NORMAL OIL CHANGE INTERVALS. INTERNAL FILTER—25,000 MILES OR 12 MONTHS OIL—25,000 MILES OR 12 MONTHS	DEXRON II
7.	*5,000 MILES OR 6 MONTHS	—	STEERING LEMACH (DRAG ROD)	2-FITTING	HLGI GRADE NO. 2

KEY	SERVICE PERIOD	CHECK	DESCRIPTION	GENERAL INSTRUCTION	RECOMMENDED LUBRICANT
8.	*50,000 MILES OR 12 MONTHS	—	FRONT AXLE	4-FITTING REQUIRED	HLGI GRADE NO. 2
9.	*15,000 MILES OR 12 MONTHS	—	PROPELLOR SHAFT UNIVERSAL JOINT	1-FITTING—EACH JOINT USE LOW PRESSURE	HLGI GRADE NO. 2
10.	*15,000 MILES OR 12 MONTHS	—	PROPELLOR SHAFT SLIP JOINT	1-FITTING—USE LOW PRESSURE	HLGI GRADE NO. 2
11.	25,000 MILES	—	STEERING COLUMN UNIVERSAL	1-FITTING—ACCESS THROUGH LEFT HAND FRONT ACCESS PANEL	HLGI GRADE NO. 2
12.	*25,000 MILES OR 6 MONTHS	—	DRAXLE SHAFT	6-FITTING	HLGI GRADE NO. 2
13.	*25,000 MILES OR 6 MONTHS	—	DRAXLE SLACKADJUSTER	6-FITTING	HLGI GRADE NO. 3 (SPECIAL STOPMASTER GREASE)
14.	*25,000 MILES OR 12 MONTHS	—	TIE ROD ENDS	2-FITTING—OIL INSIDE SWAYBAR ARM ASSEMBLY	HLGI GRADE NO. 2

* WHICHEVER OCCURS FIRST

MATERIAL:

PLAT USE:

FINISH: COLOR OR TYPE

PLATE: PLATING:

PREPARED: MILLIMETER / INCH DO NOT SCALE

ALTERNATE: DO NOT SCALE

SCALE: 1:1

DATE: 2-8-64

BY: [Signature]

REV.	DESCRIPTION	DATE	BY
1	UPDATED FOR 1951, CEN 9999	10/24/51	JK
2	CORRECTED & UPDATED	1/27/52	JK
3	UPDATE FOR 1955, CEN 4607	1/27/55	JK
4	TR PD LUBE RE-NAME	1/27/55	JK
5	CHANGE GENERAL INSTRUCTION	1/27/55	JK
6	EXTERNAL FILTER, INTERNAL FILTER FOR FET 6, FROJ 3934	1/27/55	JK
7	ADDED WORD "TEXACO"	1/27/55	JK
8	NAVOLIN UNDER RECOMMENDED LUBRICANT FOR REV. C, FROJ 3934	1/27/55	JK
9	CHANGED SERVICE PERIOD FOR REV. C PER FROJ 3934	1/27/55	JK
10	ADDED KEY IS PER FROJ 3934	1/27/55	JK

RELEASED FOR: BLUE BIRD BODY CO. PORT VALLEY, GEORGIA, U.S.A.

SCALE: 1:1

DATE: 2-8-64

BY: [Signature]

1155159